



Select 8

Copeland[™]
brand products



EMERSON[™]



Project Report

Project Details: New Project

Contact:

Author Name:

Refrigerant	R404A Dew Point
High Side Properties:	
Condensing Temperature, °C	45.82
Condensing Abs. Pressure, bar	20.86
Dew Point, °C	45.82
Bubble Point, °C	45.49
Saturated vapour enthalpy, kJ/kg	381.36
Specific volume of saturated vapour, dm³/kg	8.30
Liquid Temperature, °C	49.70
Liquid enthalpy, kJ/kg	276.83
Low Side Properties:	
Evaporating Temperature, °C	-25.00
Evaporating Abs. Pressure, bar	2.50
Dew Point, °C	-25.00
Bubble Point, °C	-25.67
With vapour at, °C	-15.00
Specific volume, dm³/kg	81.63
Enthalpy, kJ/kg	360.46
Operating Conditions:	
Evaporating Temperature, °C	-25.00
Suction Superheat, K	10.00
Ambient, °C	35.00
Condensing Unit Selected	ZXLE040E-TFD

Additional restrictions, please see application guidelines

PERFORMANCE AT SPECIFIED OPERATING POINT
ZXLE040E-TFD Data at 50Hz

Cooling Capacity, kW	5.40
Total Power Input, kW	3.80
COP	1.42
Current at 400 V, A	5.89
Mass Flow, g/s	39.40
Heat Rejection, kW	8.89
Condensing Temperature, °C	45.80

CONDENSING UNIT MECHANICAL AND PHYSICAL DATA

Condenser/Fan Type	ZX040E/60 W
Base mounting (hole dia), mm	580 x 388 (12)
Number of Fans	1
Air Flow, m ³ /s	0.81
Total Fan Power Input, W	116
Height, mm	840
Depth/Width, mm	1035/446
Suction Diameter, inch	7/8
Liquid Line, inch	1/2
Suction Type	Cu Tube
High Side PS gauge, bar	28.8
Receiver Capacity, l	4.1
Sound Pressure @ 10m, dBA	40
Low Side PS gauge, bar	21
Net Weight, kg	93

CONDENSING UNIT ELECTRICAL DATA (380-420 V / 3~ / 50 Hz)

Compressor Maximum Operating Current, A	9.2
Compressor Locked Rotor Current, A	51.5

Additional restrictions, please see application guidelines

ACCESSORIES INCLUDED

Crankcase Heater	70 W External
Oil separator	ALCO OSH-404
Liquid sight glass	ALCO MIA 012
Compressor contactor	18 A
Control circuit fuse	S7-904-5355-0
HP Switch	ALCO PS3 WDS (Automatic reset)
Electronic controller	Emerson XCM25D
Filter Drier	ALCO ADK Plus
Vapour Injection	Expansion Valve
Circuit breaker, over current relay	10 A
Suction Accumulator	ALCO A09-507

ACCESSORIES OPTIONAL

LP Adjustable Pressure Switch	Alco PS1-A3A
-------------------------------	--------------

Additional restrictions, please see application guidelines

